



FILTERING ESCAPE DEVICE



The EVAMASQUE is a light and compact 15 minutes filtering escape device which provides effective protection during the evacuation of accidentally polluted areas which volume of oxygen in atmosphere is more than 17%.

It is particularly suited to the conditions of use in Oil & Gas and chemical industries due to its broad spectrum gas filtration coverage with the ABEK filter.

The EVAMASQUE filtering escape device is safe, convenient and easy to use.



Oil & Gas



Chemical

The EVAMASQUE filtering escape device is only intended for use in emergency situations (compliant with the DIN58647-7 standard).

With a robust red protective casing, made in high impact polystyrene (HIPS), the product is protected from shocks to ensure the integrity of the half-mask and the filter.

The EVAMASQUE filtering escape device has been designed for a long lifetime with minimum maintenance: It can be stored during 12 years. The ABEK filter must be changed every 4 years to ensure full efficiency.

The others components (half-mask and protective casing) are also available for change if required.

PROTECTION

- The EVAMASQUE filtering escape device provides a high level of protection due to its ABEK filter. Its filter provides a broad spectrum protection against organic, inorganic gases and vapours, sulphur dioxide,

hydrogen chloride and other acid gases, ammonia and organic ammonium compounds.

SAFETY

- The filtering escape device can be worn around the waist belt, always within hand reach in case of an emergency: the user only has to open the protective casing and put it on.
- The EVAMASQUE filtering escape device is packed inside a robust protective casing which protects the filtering escape device against accidental damage and contamination.
- The EVAMASQUE can only be used in atmosphere with more than 17% of oxygen.

COMFORT AND CONVENIENCE

- The user's field of vision is not obstructed due to the low position of the filter on the half-mask.

- The exhalation valve reduces the breathing resistance, providing better comfort. This point is very important in a situation of evacuation as, in such a case, the breathing rate increases.
- Compact, light and worn around the waist belt it does not disturb the user during its work.



SPECIFICATIONS	
Gross weight (with casing) / Net weight (without casing)	440 gr / 365 gr
Product dimensions / Packaging dimensions	15,4 x 10,5 x 8 cm / 16 x 15 x 13 cm - individual packed
Standard	DIN 58647-7
Protection factor	NFP (nominal factor protection) : 50 / AFP (assigned factor protection) : 10

MATERIAL	
Skirt	Black EPDM
Inhalation Valve / Exhalation Valve	Neoprene / Black Silicone
Filter	ABEK Charcoal, aluminium casing
Box	Red high impact polystyrene
Strap	Elastomeric
Adhesive tape	Coated textile

ORDERING INFORMATION	PART NUMBER
EVAMASQUE complete with filter	17 285 70
ABEK replacement anti-gas filter (includes seal strip + elastic strap)	17 285 71
Protective box (with beltclip and strap)	17 799 93
Adhesive tape - 50 meters (allows for sealing of about 90 units)	17 288 21
100 x disinfecting wipes	17 266 02
EVAMASQUE alone with elastic strap and no filter	17 285 02

HONEYWELL SAFETY PRODUCTS

SPERIAN PROTECTION (UK) LIMITED

Unit 3 Elmwood, Chineham Park,
Basingstoke, RG24 8WG
Phone: +44 (0) 1256 693 200
Fax: +44 (0) 1256 693 300
E-mail : hrsp-info@honeywell.com

www.honeywellsafety.com

HONEYWELL SAFETY PRODUCTS EUROPE SAS

Immeuble Edison Paris Nord 2
33 rue des Vanesses
CS 55288 Villepinte
95958 Roissy CDG Cedex - France
Tel : +33 (0)1 49 90 79 79
Fax : +33 (0)1 49 90 71 04
Email: info-export.hsp@honeywell.com

Honeywell

DOC3054
For further information, visit www.honeywellsafety.com
©2012 Honeywell International Inc. All rights reserved.